



Inline Flow Meter 534FTB FOR EXCEPTIONAL ACCURACY



Kurz 534FTB inline flow meters for industrial gas flow measurement are designed to eliminate the need for field fabrication and assembly of inlet and outlet piping sizes by providing accurate gas flow measurement under changing upstream and downstream flow profiles. Built-in reducers/expanders result in exceptional immunity to upstream and downstream flow disturbances caused by valves, bends, and short straight runs.

The patented design produces very low flow noise and provides exceptional accuracy and repeatability, and it supports a high turn-down ratio. Kurz thermal mass inline flow meters deliver incredibly fast response to temperature and velocity changes.



Kurz Instruments, Inc.
2411 Garden Road
Monterey, CA 93940
800-424-7356
www.KurzInstruments.com



SPECIFICATIONS

- **Mass flow range**
Up to 7,016 SCFM (10,944 NCMH)
depending on model and calibration option
- **Flow accuracy** (SCFM at laboratory conditions)
 \pm (1% of reading + (A x 20 SFPM))
where A is the flow area of the 534FTB
- **0.25% reading repeatability**
- **Velocity time constant**
1 second for velocity changes at
6,000 SFPM (constant temperature)
- **Process temperature time constant**
8 seconds for temperature changes at
6,000 SFPM (constant velocity)
- **Temperature accuracy**
 \pm (0.5% of reading +1°C) for
velocities above 100 SFPM
- **Electronics operating temperature**
Integral display
-13°F to 149°F (-25°C to 65°C)
Remote aluminum enclosure
-40°F to 149°F (-40°C to 65°C)
Remote polycarbonate enclosure
-13°F to 122°F (-25°C to 50°C)
- **Process pressure rating**
Up to 300 PSIG (20 BARg)
- **Process temperature rating**
-40°F to 257°F (-40°C to 125°C)

FEATURES

- **Aluminum (Type 4, IP66) dual-chamber polyester powder-coated enclosure**
- **Eight models available in pipe diameters from 1/2" to 8"**
- **Adjustable display/keypad orientation**
- **Optically-isolated loop-powered 4-20 mA output**
- **Integral or remote user interface**
- **Easy-to-use interface**
- **User-configurable flow display (scrolling or static)**
- **User-configurable English or metric units for mass flow rate, mass velocity, or process temperature**
- **Two optically isolated solid-state relays / alarms**
- **Built-in flow totalizers and elapsed time**
- **Configuration/data access via USB or RS-485 Modbus (ASCII or RTU)**
- **3-year warranty**

APPROVALS

- **EPA mandatory GHG certification**
40 CFR 98.34(c)(1)
- **Alarm output conformity**
NAMUR NE43
- **CE and UKCA compliance**
EMC, LVD, PED, ROHS, and WEEE
- **cETLus, ATEX, UKEX, IECEx approvals for Explosive Atmospheres protection by Flameproof and Increased Safety**
EN/IEC/UL/CSA C22.2/60079-0
EN/IEC/UL/CSA C22.2/60079-1
EN/IEC/UL/CSA C22.2/60079-7
Class I, Div. 1, Group B, C, and D
Class I, Div. 2, Group A, B, C, and D

OPTIONS

- **Enclosures**
Aluminum or remote-only stainless steel or polycarbonate
- **Multiple gas calibrations with up to five curves loaded in memory**
- **User-defined binary gas composition**
- **Hardware accessories**
- **Communication protocols**
HART (v7 FSK) and PROFIBUS DP
- **SIL1 certification**
via TUV Rheinland

534FTB Benefits

The 534FTB is ideal for accurate high-pressure gas flow measurements, and includes the qualities and features found in all Kurz thermal mass flow meters.

- **Built-in flow conditioners to accommodate upstream and downstream flow disturbances**
- **Ideal for process and specialty gases**
- **Exceptional low end-to-end pressure drop**
- **Very low flow noise**
- **Sensors resistant to dirt and corrosion**
- **Wide turndown capability**
- **Zero velocity as a valid data point**

The Kurz Advantage

Kurz Instruments is dedicated to manufacturing and marketing the best thermal mass flow meters available and to support our customers in their efforts to improve their businesses.

In this effort, we provide:

- **The highest repeatability, accuracy, and reliability available**
- **The fastest response to temperature and velocity changes in the industry**
- **Continuous self-monitoring electronics that verify the integrity of sensor wiring and measurements**
- **Sensors that do not overheat at zero flow using a patented constant temperature control method and power limiting design**
- **Velocity-temperature mapping for wide ranging velocity and temperature**